

## Lockie

for child restraints

Part No: CS107

**INSTALLATION AND INSTRUCTIONS FOR USE ON A LAP-SASH VEHICLE SEAT BELT WHEN INSTALLING CHILD SEATS WITH AN INBUILT HARNESS. THIS PRODUCT IS NOT REQUIRED FOR CHILD SEATS INSTALLED USING ISOFIX CONNECTIONS OR IN VEHICLE SEATING POSITIONS WHERE ONLY A LAP BELT IS PRESENT.**

This device has been designed to cater for most vehicle seat belts however there may be a small number of vehicles

for which it is not compatible. Please do not use this product if you cannot insert the keel of the device into the buckle tongue far enough to keep the vehicle seat belts firm around your child seat.

**IMPORTANT:** Use this product only in accordance with these instructions. Do not use this product with a booster seat, an accessory child harness or a convertible booster

seat being used in booster seat mode. It may be possible for some seat belt movement to take place over time, even when using this product. Check the seat belts holding your child restraint for connection and correct tension every time you drive.

### Instructions

**(a)** Place your child seat into the vehicle and pass the seat belt through the path according to the manufacturer's instructions. Connect

the vehicle seat belt buckle tongue to the vehicle seat belt buckle and listen for a 'click'.

**(b)** Gently push down on the child seat. At the same time pull the sash portion of the vehicle seat belt as shown by 1 until all slack has been removed from the vehicle lap belt section and the child seat is firm in the car.

**(c)** Keep holding the sash belt and align the thin keel on the underside of the

110mm

35mm

35mm


35mm

35mm

Lockie device to the seat belt buckle tongue slot as shown by 2.

**(d)** Using your thumb, push the keel of the Lockie device into the buckle tongue slot as far as it will go. Don't worry if it doesn't go all the way in, so long as it is tight and the seat belt stays firm.

**(e)** Release your grip on the sash belt and feed any excess slack into the inertia reel of the vehicle. The Lockie device should remain firm in the buckle tongue slot as shown by 3. The lower seat belt holding the child seat should also be firm.



## Infasure Warranty Details

Infasure Pty Ltd warrants this product for twelve months from the date of purchase against failure due to manufacturing faults or faulty materials. Misuse, accidental damages, normal wear and tear are not covered by this warranty. When used for commercial use the period is limited to six months. "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure."

Refer to website for details:  
[www.infasure.com.au](http://www.infasure.com.au)

## Infasure Customer Care

**Phone No:**  
+61 2 4728 8090

**Fax No:**  
+61 2 4728 8040

**Email:**  
[service@infa.com.au](mailto:service@infa.com.au)



**INFASURE PTY LTD**  
P.O. Box 487,  
Emu Plains NSW 2750  
PH: 02 4728 8090

🏠 [infasure.com.au](http://infasure.com.au)  
📷 [instagram.com/infasure](https://www.instagram.com/infasure)  
📘 [facebook.com.au/infasure](https://www.facebook.com.au/infasure)  
📺 [youtube.com.au/infasure](https://www.youtube.com.au/infasure)

ISSUE: D

110mm

35mm

35mm

35mm

35mm